

# **Epilog**Laser



# OVER 30 YEARS OF EXPERIENCE




In 1988, Epilog Laser's revolutionary systems opened the world's eyes, not only to what could be accomplished with a laser, but also to how accessible a laser is to businesses, both large and small.

We are innovators. We are engineers. We are problem solvers. We are committed to designing and manufacturing the highest-quality, fastest laser systems in the industry, right here from our global headquarters in Golden, CO, in the foothills of the Rocky Mountains.

Our worldwide presence continues to grow with corporate offices located in the Netherlands and Canada. We now have even more locations to provide you with the highest level of support and convenience. Contact us to schedule a hands-on demonstration from your local distributor and see how an Epilog Laser can benefit your business with the industry's highest engraving speeds, the most-detailed etching, and fast, accurate cutting. Find out how an Epilog Laser can transform your business.













# ENGRAVE - CUT - MARK

Electronics Engraving
Wood Engraving & Cutting
Marble & Stone Etching
Acrylic & Wood Signage
Nameplates & Desk Sets
Wedding Memorabilia
Corporate Giveaways
Glass Etching
Sporting Goods

Holiday Ornaments
Corporate & Sporting Awards
Architectural Models
One-of-a-Kind Gifts
Greeting Cards
Guitar Inlays
Custom Jewelry
Acrylic Plaques
Photo Frames

3D Models
Inlaid Signage
Photo Engraving
Barcode Engraving
Engraved Denim Jeans
Logo Engraving on Parts
Etched Business Cards
Tool Identification
Medical Part Markina

Laptop Customization
Paper Invitations
Marble Flooring
Cloth Etching
Memorials
Home Decor
Cabinetry
Product Marking
Industrial Etching

Phone Customization Custom Pet Tags Appliqués Toys & Games Photo Albums Wine Bottle Etching Engraved Mirrors Photo Etching And much more!

# CHOOSE YOUR LASER

#### CO<sub>2</sub>: Versatility

Engrave and cut a wide variety of materials with our CO<sub>2</sub> laser line. A CO<sub>2</sub> laser system can engrave on all kinds of materials, including wood, acrylic, rubber, plastic, and more.

	Engrave	Cut
Wood	•	
Acrylic	•	
Glass	•	
Coated metals	•	
Ceramics	•	
Delrin	•	•
Cloth	•	•
Leather	•	•
Marble	•	
Matboard	•	•
Melamine	•	•
Paper	•	•
Mylar	•	•
Cardboard	•	•
Rubber	•	•
Wood veneer	•	•
Fiberglass	•	•
Painted metals	•	
Tile	•	
Plastic	•	•
Cork	•	•
MDF	•	•
Anodized aluminum	•	
Twill	•	•
Stainless steel	‡	
Brass	‡	
Titanium	‡	
Bare metal	‡	

#### Fiber: Metal Etching

Featuring an air-cooled ytterbium fiber laser source, these are the ideal systems for direct metal etching and marking, as well as marking engineered plastics.

#### Compatible Materials:

ABS (black/white) Aluminum 6061 Aluminum, yellow chromate Anodized aluminum Bavers bavblend FR110 Brass Brushed aluminum Carbon fiber Carbon nanotube Ceramics Ceramics, metal-plated Cobalt chrome steel Copper DAP- Diallyl Phthalate Delrin, colored (black/brown) GE Plastics polycarbonate resin Hard coat anodized aluminum Inconel metals (various) Iron-phosphate coating Machine tool steel Magnesium Makrolon

Makrolon 2807

Molybdenum

Nickel-plated 1215 mild steel Nickel-plated brass Nickel-plated gold Nickel-plated Kovar Nickel-plated steel Nvlon PEEK, white & glass filled Polybutylene Terephthalate Polycarbonate, (black/white) Polycarbonate resin 121-R Polysulfone Rynite PET Santoprene Silicon carbide Silicon steel Silicon wafers Stainless steel 303 Stainless steel 17-4 PH Steel 4043 Steel, machine tool Teflon, glass filled Various inconel metals Zinc-plated mild steel And many more!

‡ CO2 lasers will mark bare metals when coated with a metal marking solution. For more info, call +1 303-277-1188

# FASY PROJECT SETUP

## From Design to Finished Product



Design your graphic in your favorite graphic design software.



Print the design to the Epilog Laser Dashboard™.



Choose your settings and start engraving or cutting your design.

### Material Settings Library

Epilog's Material Settings Library is your first stop for finding the perfect settings for most materials. This parameter library has been built by testing materials to find the best settings for you to use with your laser system. If you discover your own preferred settings, or have a special material that you use with your laser, save your custom settings so you always have access to your favorite laser parameters at the touch of a button.

#### Online Training

Register your machine at our free online training suite, training.epiloglaser.com and start learning the latest tips and tricks on project setup and more. Featuring walkthrough demonstrations of how to set up projects, articles on maintenance for your machine, and a thorough library of support videos, the Epilog Laser Training Suite is your online manual for learning how to make the most of your laser system.

### IRIS™ Camera Positioning & Job Trace


Positioning your image for engraving has never been easier. The Fusion Pro's IRIS™ multi-camera system shows your laser's table on screen in the Laser Dashboard™, allowing you to precisely position your image on screen, then print to the laser. You can also use the camera at the laser head to recognize registration marks in your artwork for extremely precise engraving on preprinted pieces. To ensure your engraving is precisely positioned, run the instant Job Trace to see exactly where your image will be engraved on your product.


## Fastest Engraving Speeds: Up to 165 IPS (4.2 m/s)

Higher-speed engraving means more throughput for your business. Epilog prides itself on creating machines with incredibly fast engraving times and the quickest turnaround speeds, while still providing the highest quality results. The Fusion Pro's new motion control system allows the laser to reach a top speed of 165 IPS with 5g acceleration for the industry's fastest engraving. Extremely robust motors and an industrially designed motion control system allow us to reach the highest engraving speeds while still providing the high-resolution you expect from an Epilog Laser.

## Epilog Software Suite™

Epilog's powerful software suite allows you to position your artwork and duplicate your image across the screen, and access our materials database quickly and easily. Save your files to the Job Manager and you can access any job you have ever sent to the laser. Organize your jobs, rerun projects, and more.







# ZING LASERS





#### ZING 16

Small-size, entry-level laser system that is perfect for starting a business or operating out of your home, office, or school.

- 30 or 40 watt CO<sub>2</sub> laser
- 16" x 12" x 4.5" (406 x 305 x 114 mm) work area
- · Affordable pricing for the entry-level user


#### ZING 24

Larger work area and more features make this laser an affordable choice for those needing more features than an entry-level machine.

- 30, 40, 50, or 60 watt CO<sub>2</sub> laser
- · 24" x 12" x 7.75" (610 x 305 x 197 mm) work area
- · Compatible with the Rotary Attachment
- Radiance™ Beam-Enhancing Optics for a smaller laser spot size across the table


### System Features

	Zirig io	ZII 19 Z4
Made-in-the-USA Quality: Designed, engineered & built in Golden, CO	•	•
Epilog Job Manager: Management & workflow software - easily organize, edit, save & print	•	•
Laser Dashboard™: Set speed/power parameters & access more laser features	•	. 1
CO <sub>2</sub> Laser Tubes: Long-lasting metal/ceramic tubes for highest engraving quality		•
Lenses Rated to 500 Watts: Highest-quality lenses provide long life & higher resolutions	•	•
High-Speed Stepper Motors: Faster stepper motors for high-resolution engraving		•
3D & Stamp Engraving Settings: Etch & cut stamps or create 3D curves while engraving		
Super-Silent™ Cooling Fans: Quiet operation suitable for office environments	•	
Air Assist: Remove heat & combustible gases from the cutting surface		•
Raster/Vector Color Mapping: Change your speed & power by using color settings		•
Networking Choices: USB & Ethernet connections		
Moveable Home Position: Engrave odd-shaped items easily by setting a new home position		•
Red Dot Pointer: Provides a visible laser beam to help position projects	•	
Easy-Access Drop-Down Door: Front access door for the laser system		•
Radiance™ Beam-Enhancing Optics: Higher-resolution optics for detailed engraving		•
Rotary Attachment Compatibility: Engrave cylindrical objects with the optional rotary		



Zing 16 Zing 24





# MINI & HELIX LASERS



#### MINI 18 & 24

Looking for a system with faster engraving times than the Zing Series, but that still offers a small work area? The Epilog Mini 18 and 24 Lasers are an ideal way to move into our faster servo motor machines.

- 30 or 40 watt CO<sub>2</sub> laser Mini 18
- 30, 40, 50, or 60 watt CO<sub>2</sub> laser Mini 24
- 18" x 12" x 4" (457 x 305 x 102 mm) work area Mini 18
- 24" x 12" x 5.5" (610 x 305 x 140 mm) work area Mini 24
- · High-speed servo motors and linear encoder driven
- Automatic focusing



#### HELIX

For engravers and cutters looking to work with larger pieces or products, the Epilog Helix is an ideal choice.

- 30, 40, 50, 60, or 80 watt CO<sub>2</sub> laser
- 24" x 18" x 8.5" (610 x 457 x 216 mm) work area
- Radiance™ Beam-Enhancing Optics for a smaller laser spot size across the table
- Easy-access drop-down door
- Engrave items up to 11" (279 mm) tall
- Wheeled storage stand

# System Features

Made-in-the-USA Quality: Designed, engineered & built in Golden, CO	•	•	•
Epilog Job Manager: Management & workflow software - easily organize, edit, save & print		•	•
Laser Dashboard™: Set speed/power parameters & access more laser features	•	•	•
CO2 Laser Tubes: Long-lasting metal/ceramic tubes for highest engraving quality	•	•	•
Auto Focus: Automatically focus the table to the correct focal distance			
Integrated Cutting Table: Lifts the piece being cut to reduce back-side burning			
Moveable Home Position: Engrave odd-shaped items easily by setting a new home position			
Red Dot Pointer: Provides a visible laser beam to help position projects			
Rotary Attachment Compatibility: Engrave cylindrical objects with the optional rotary			
Raster/Vector Color Mapping: Change your speed & power by using color settings			•
Networking Choices: USB & Ethernet connections			
Permanent Job Storage: Store as many as 10 jobs up to 2MB in size			•
Job Delete at the Laser: Delete old jobs to keep laser job queue organized			•
Radiance™ Beam-Enhancing Optics: Higher-resolution optics for detailed engraving			•
Lenses Rated to 500 Watts: Highest-quality lenses provide long life & higher resolutions			
Linear Encoders: Highest-quality engraving from the most precise motion control system			•
High-Speed Servo Motors: Faster servo motors for high-resolution engraving			
3D & Stamp Engraving Settings: Etch & cut stamps or create 3D curves while engraving			•
Super-Silent™ Cooling Fans: Quiet operation suitable for office environments			
Air Assist: Remove heat & combustible gases from the cutting surface			•
Metal Bearings: Stainless steel bearings designed to last the life of the machine			•
Kevlar Belts: Our precision drive belts are made from B-style Kevlar for superior longevity			•
Crumb Tray: Easily dispose of debris from under your Cutting Table			
Easy-Access Storage Stand: Wheeled, free-standing cart for easier access			

Mini 18 Mini 24 Helix

# FIBERMARK S2 LASER



#### FIBERMARK S2

Our small-format fiber laser system, the FiberMark S2, allows you to etch directly into metal and mark many plastics. The FiberMark S2 is our original fiber laser system and is the first flying-optic fiber laser system ever developed.

- 30 watt fiber laser
- 24" x 12" x 5.5" (610 x 305 x 140 mm) work area
- Easy-Access Drop-Down Door
- · Ability to create etched, annealed, and polished marks
- 75-1200 dpi

#### Small-Format Metal Marker

Epilog's FiberMark S2 is your solution for etching and marking all types of bare metals and industrial plastics. Print to the laser directly from any graphic software program for easy job setup, and etch an entire table full of parts at one time.

- · Directly engrave on most metals
- Mark engineered plastics
- Etch barcodes, serial numbers, and images
- · Print directly from AutoCAD, CorelDRAW, Bartender, and more



FiberMark

### System Features

	HIDOHMOHIC
Made-in-the-USA Quality: Designed, engineered & built in Golden, CO	
Epilog Job Manager: Management & workflow software - easily organize, edit, save & pri	int •
Laser Dashboard™: Set speed/power parameters & access more laser features	•
Fiber Laser Source: Etches directly into bare metal & marks industrial plastics	
Moveable Home Position: Engrave odd-shaped items easily by setting a new home position	on •
Red Dot Pointer: Provides a visible laser beam to help position projects	•
Rotary Attachment Compatibility: Engrave cylindrical objects with the optional rotary	
Raster/Vector Color Mapping: Change your speed & power by using color settings	
Networking Choices: USB & Ethernet connections	•
Permanent Job Storage: Store as many as 10 jobs up to 2MB in size	
Job Delete at the Laser: Delete old jobs to keep laser job queue organized	•
Linear Encoders: Highest-quality engraving from the most precise motion control syste	· m
High-Speed Servo Motors: Faster servo motors for high-resolution engraving	
3D & Stamp Engraving Settings: Etch & cut stamps or create 3D curves while engraving	9 .
Super-Silent™ Cooling Fans: Quiet operation suitable for office environments	•
Air Assist & Compressor: Remove heat & combustible gases from the cutting surface	•
Metal Bearings: Stainless steel bearings designed to last the life of the machine	
Kevlar Belts: Our precision drive belts are made from B-style Kevlar for superior longevity	

# FUSION PRO LASERS





- Available in CO<sub>2</sub>, fiber, or dual-source configurations
- 50, 60, 80, or 120 watt CO<sub>2</sub> laser
- 30 or 50 watt fiber laser
- 32" x 20" (812 x 508 mm) work area
- IRIS™ 2-camera system



#### FUSION PRO 48

- Available in CO<sub>2</sub>, fiber, or dual-source configurations
- 50, 60, 80, or 120 watt CO<sub>2</sub> laser
- 30 or 50 watt fiber laser
- 48" x 36" (1219 x 914 mm) work area
- IRIS™ 3-camera system

## Industry's Highest-Speed Engraving

Introducing the fastest laser engraving systems on the market. Performance and image quality are at the heart of the Fusion Pro line of laser systems. With a maximum speed of 165 IPS (4.2m/s), and featuring 5g acceleration, the Fusion Pro lasers are the fastest, most productive laser systems available. Whether you're engraving wood, plastic, coated metals, or glass, the Fusion Pro allows you to produce more product in less time than any competitive system.

### IRIS™ Camera Positioning

Positioning your artwork is easier than ever with the new IRIS™ Camera Positioning feature of the Fusion Pro. Overhead cameras provide a view of your material as it is positioned on the table, allowing you to accurately place your artwork and know exactly where your laser will engrave. Drag and drop your artwork on screen to precisely position your artwork on even the most irregularly shaped objects.

#### System Features

	Pro 32	Pro 48
Made-in-the-USA Quality: Designed, engineered, & built in Golden, CO	•	•
High Speed Engraving: Max speed of 165 IPS (4.2 m/s)	•	
5g System Acceleration: Fast acceleration to top speed		
IRIS™ Camera Positioning: Overhead cameras & camera at the carriage for artwork positioning	•	
SAFEGUARD™ features: Keep the mechanics cleaner and dust-free		•
Touch-Screen Control: File selection, auto-focus, and more		
Air Assist & Compressor: Remove heat & combustible gases from the cutting surface		
Vacuum Hold-Down Table: Exhaust under the table	•	
Networking Choices: USB & Ethernet connections		
Permanent Job Storage (1 GB): Keep your most-run jobs at the machine	•	
Auto Focus: Automatically focus the table to the correct focal distance	•	•
Software Suite: Dashboard™ and Job Manager Software Package	•	•
50, 60, 80, or 120 watt CO <sub>2</sub> , air-cooled, metal/ceramic laser tube, 10.6 micrometers	•	
or 30 or 50 watt Fiber Laser Source, 1064 nm	•	•
or Dual Source configuration	•	
Radiance™ Beam-Enhancing Optics: Higher resolution optics for detailed engraving	•	•
Laminar Air Flow: Streamlined air flow for the most efficient smoke and vapor removal	•	
High-Speed, Brushless DC Servo Motors: Withstands the most rigorous engraving jobs at high speeds	•	•
Red Dot Pointer: Provides a visible laser beam to help position your projects	•	
Job Trace: Quickly see where the job will engrave on your material	•	•
Easy-Access Drop-Down Door: Front access door for the laser system		•
Super-Silent™ Cooling Fans: Quiet operation suitable for office environments	•	•
Rim-style Rotary Compatibility	•	•



# ACCESSORIES

#### Air Compressor

Epilog's optional Air Compressor is available to work with the included Air Assist feature of the laser systems. Direct a constant stream of air to your cutting surface to remove heat and combustible gases from the work area. This high-quality air compressor unit feeds 30 psi (2.07 bar) of air through the Air Assist structure, giving you the best cutting results available. The vibration-dampening rumber feet reduce the noise level of the compressor.

## Cutting Tables

Incorporate the gridded cutting table when cutting through materials. By raising the materials off of the table when cutting, you'll be able to reduce any back-side burning on the material.

For cutting through materials on the Fusion Pro, choose between a traditional cutting-grid table or a slat table.

### Rotary Attachments

Add the ability to engrave cylindrical items to your laser, including glasses, bottles, and more. Epilog offers two types of Rotary Attachments. The Standard Rim-Style Rotary is great for general-purpose cylindrical shapes, including glasses, mugs and wine bottles. We offer the 3-Jaw Chuck Rotary Attachment for more demanding applications when you need to mechanically clamp a cylinder or oddly shaped, non-cylindrical item.











### Lens Options

1.5" Lens: Highest-Resolution Engraving

Although the standard 2.0" lens provides amazing detail, our 1.5" lens assembly has been designed for the highest-resolution engraving and etching of extremely small fonts.

4.0" Lens: Cutting Thicker Materials and Inside Deep Areas

The 4.0" lens produces a focused beam over a longer vertical distance, which makes it ideal when engraving within a recessed area of a product, such as inside a bowl or plate. The lens is also useful for cutting through very thick materials with a more elongated beam.

#### Machine Stand

Add the machine stand to your Mini or FiberMark S2 to turn your desktop laser into a free-standing unit. This optional stand features high-quality wheels to move the laser system throughout your work area with ease, and the shelf makes a great place to store your most used materials.

#### Pin Table

The Pin Table incorporates moveable pins designed to raise and support material during cutting. This helps ensure you receive the cleanest laser cut edges from your laser machine. Use the Pin Table with the Fusion Pro's  $IRIS^{TM}$  camera system for a visual representation of each pin's precise location for the highest quality edge cuts on a laser system.







16









MINI
Mini 24

	21119 10	21119 24	741111110	/VIII II 24	
Work Area	16"x12" (406x305 mm)	24"x12" (610x305mm)	18"x12" (457x305mm)	24"x12" (610x305mm)	
Max Material Thickness	4.5" (114mm)	7.75" (197mm)	4" (102mm). Remove table for 6" (152mm) depth & 17.5"x10" (444x254mm) work area	5.5" (140mm). Remove table for 8" (203mm) depth & 23.5"x11.75" (597x298mm) work area	
Laser Tube Wattages	30 & 40 watt, CO <sub>2</sub> , air-cooled, metal/ ceramic tube, 10.6 micrometers	30, 40, 50 & 60 watt, CO <sub>2</sub> , air-cooled, metal/ceramic tube, 10.6 micrometers	30 & 40 watt, CO <sub>2</sub> , air-cooled, metal/ ceramic tube, 10.6 micrometers	30, 40, 50, & 60 watt, CO <sub>2</sub> , air-cooled, metal/ceramic tube, 10.6 micrometers	
Software	Laser Dashboard™, Epilog Job Manager™				
Memory	Multiple files up to 64MB. Engrave any file size				
Modes	Optimized Raster, Vector & Combined mode				
Motion Control	High-speed micro stepper motors		High-speed, continuous-loop, DC servo motors using linear and rotary encoding technology for precise positioning		
X-Axis Bearings	Shielded roller bearing assembly on a	a ceramic-coated aluminum guide rail	Ground & polished stainless steel long-lasting bearing system		
Belts	Advanced B-style Kevlar belts		Advanced B-style double-wide Kevlar precision drive belts		
Resolution	User-controlled 100-1000dpi		User-controlled 75-1200dpi		
Speed & Power	Computer-controlled speed & power feature links Speed, Power, Frequency color	in 1% increments up to 100%. Color mapping /, & Raster/Vector mode settings to any RGB	Computer-controlled speed & power in 1% increments up to 100%. Color mapping feature links Speed, Power, Frequency, Raster/Vector mode, & Air Assist On/Off settings to any RGB color		
Print Interface	USB & 10Base-T Ethernet connections. Windows 7/8/10 compatible				
Size (W x D x H)	28.75"x22.125"x12.5" (730x562x318mm)	38"x27.25"x15" (965x692x381mm)	27.8"x26"x13.5" (706x660x343mm)	34.5"x26"x16" (876x660x406mm)	
Weight	95lbs (43kg)	140lbs (64kg)	70lbs (32kg)-100lbs (45.5kg) with stand	90lbs (41kg)-120lbs (55kg) with stand	
Electrical	Auto-switching power supply 110-240volts, 50 or 60Hz, single phase				
Ventilation System	350-400CFM (595-680m³/hr) external exhaust to outside or internal filtration unit required. One output port, 4" (102mm) in diameter				
Class	Class 2 Laser Product - 1 mW CW MAXIMUM 600-700nm				
	Class 2 Easter 1 Todas C 1 111W GW M-Adilholm 600 700 film				









Helix	FiberMark S2	Fusion Pro 32 (CO <sub>2</sub> )	Fusion Pro 32 (Fiber)	Fusion Pro 48 (CO <sub>2</sub> )	Fusion Pro 48 (Fiber)	
4"x18" (610x457mm)	24"x12" (610x305mm)	32"x20" (812x508mm)		48"x36" (1219x914mm)		
.5" (216mm). Remove table for 11" (279mm) lepth & 23.5"x17" (597x432mm) work area	5.0" (127mm)	12.25" (311mm)				
0, 40, 50, 60, & 80 watt, CO2, air-cooled, netal/ceramic tube, 10.6 micrometers	30 watt, Fiber, air-cooled, includes collimator. 1064 nm. Beam quality: M2 < 1.1	50, 60, 80, or 120 watt, CO <sub>2</sub> , air-cooled, metal/ceramic tube, 10.6 micrometers	30 or 50 watt, Fiber, air- cooled, includes collimator. 1064nm. Beam quality: M2 < 1.1	50, 60, 80, or 120 watt, CO <sub>2</sub> , air-cooled, metal/ceramic tube, 10.6 micrometers	30 or 50 watt, Fiber, air- cooled, includes collimator. 1064nm. Beam quality: M2 < 1.1	
aser Dashboard™, Epilog Job Manage	er™					
Aultiple files up to 64MB. Engrave any f	file size	Multiple Files up to 1GB. Engrave any file size				
Optimized Raster, Vector & Combined 1	mode					
ligh-speed, continuous-loop, DC servo otary encoding technology for precise	o motors using linear and e positioning	High-speed, continuous-loop	op, brushless DC servo motors using rotary encoding tech for precise positioning			
Ground & polished stainless steel long-	lasting bearing system	Ground & polished stainless steel, Teflon-coated, self-lubricating bearings. Dual blocks on X-axis for greater rigidity				
dvanced B-style double-wide Kevlar (	precision drive belts					
Jser-controlled 75-1200dpi						
Computer-controlled speed & power in Color mapping feature links Speed, Po node, & Air Assist On/Off settings to an	wer, Frequency, Raster/Vector	165 IPS (4.2m/s) with 5g acceleration. Computer-controlled in .001 increments up to 100%. Color mapping feature links Speed, Power, Frequency, & Raster/Vector mode				
USB & 10Base-T Ethernet connections. Windows 7/8/10 compatible						
6.5"x32"x39.8" (927x813x1011mm)	34.5"x24"x16" (876x622x406mm)	m) 54.6"x34.2"x42" (1387x869x1067mm) 70.6"x51.3"x42.75" (1794x1304x1086mm) Pedestal removed: 34"h (863mm)				
BOIbs max (82kg)	120lbs max (55kg) without stand	400lbs (182kg)		650lbs (295kg)		
Auto-switching power supply 110-240vo	olts, 50 or 60Hz, single phase			220/240volts, 50 or 60Hz, single p	hase	
50-400CFM (595-680m³/hr) external exl iltration unit required. One output port		One upper output port. One lower port. Total 735CFM. All ports 4" (102mm) diameter  Two upper output ports 4" (102mm) diameter		Two upper output ports. One lo ports 4" (102mm) diameter	o upper output ports. One lower port. Total 735CFM. All rts 4" (102mm) diameter	
Class 2 Laser Product - 1 mW CW MAXIMUM 600-700nm						

Technical specifications and product configurations subject to change without notice.







